EPA WEIGHTED AVERAGES CALCULATIONS EPA WEIGHTED AVERAGE PARTICULATE EMISSION RATE

	The weighted	l average parti	culate emission	rate (PM) for the
PACIF	ic ENURGY S	jummit Mo	de B Nor	icetalytic
wood	1 heater	manufactured	by PACIFIC	Energy
			i.	s 3.48 g/hr.
and the second s		TOURED AVEDA	GE OVERALL EF	FTCIENCY
4				
			ncy (80E) using	
			is %. The	CONTRACTOR OF THE STATE OF THE
				ating Value (LHV)
CSA B41	5.10-1 is	%. The EPA Def	ault efficiency	Value is 63.0 %.
EPA TEST RESULTS				
	4 10		нну	LHV
Run #	Dry Burn Rate/kq/hr	Grams/Hour	Overall <u>Efficiency</u>	Overall <u>Efficiency</u>
Kuii ii	0.938	2.883	тицијана облогој.	
	1011	3.900	· · · >	*Sold and the second se
	1042	4.039		gam-rogalishinin
	11100	3,531.		And the second s
	71700	2941	7-1-2	80.2
	2.179	Contraction of the Contraction o	E 8 6	and the same of th
a	3.189	5.736	Commission - registrate department of the commission of the commis	-
	Company of the second s			
NULL ADDRESS TO AN ANALYSIS OF THE ADDRESS OF THE A			Compression of the standard of the Compression of t	estimated that the intermight as to the January and the Control of
6	1.139	2:388	der für gegen zu seine s	audZicopyndh
				Note that the following the second distribution of the second second second second second second second second
consider-y-registry-modes confidentifether			V N N N N N N N N N N N N N N N N N N N	Name is not a representable for one originate management to the control of
	: Fan Conf	LHA DIN	Tro-	
1 KAN V	E LAW FW.			